

JAC 20m³ (Weichai) Stainless steel TANKER
USD\$107,345

- Tank volume: 20m³
- Tank material: **stainless steel** (food grade) ,5 mm
- With pump and flow meter, as well as stainless steel pipe for water supply.
- Pump capacity: 60m³/ hour (mechanical pump)

N.B. PRICES ARE SUBJECT TO CHANGE BASED
ON THE EXCHANGE RATE.





Specification for HFC1254KR1T

- 车型 Model: HFC1254KR1T
- 驱动形式 Drive mode: 6×4

主要技术参数Main technical parameters

尺寸参数Size Parameter

- 外型尺寸 Overall dimension (L×W×H) (mm) :
11200×2500×3430
- 轴距 Wheelbase (mm) : 6000+1350

性能参数 Performance Parameters

- 最高车速 Max speed (Km/h) : 90
- 最大爬坡度 Maximum Gradeability (%) : 40

主配置 Main configuration

驾驶室 Cab

- 型式 Type: Half height roof
- 座椅 Seat: air seat
- 空调 AC: 标配 Standard
- 暖风 Heater: 标配 Standard
- 电动玻璃 Electric glass: 标配 Standard
- MP3: 标配 Standard
- 驾驶室支撑形式 Cabin suspension: 2 springs in front and 2 air bags in rear
- 副驾驶遮阳板 Copilot visor: 标配 Standard
- 散热器保护架 Radiator protection frame: 带 with

发动机 Engine

- 型号 Model: WP10.340E32
- 品牌 Brand: WEICHAI
- 排放水平 Emission levels: E-III
- 额定功率/转速 Max output power (hp/rpm) : 340/2200
- 最大扭矩/转速 Max torque (N·m/rpm) : 1350/1200-1600
- 排量 Displacement (cc) : 9726

离合器 Clutch

- **形式 Mode:** 单片, 干式, 膜片弹簧式, 法雷奥
Single, dry plate, diaphragm spring, VALEO
- **规格 Specification:** $\Phi 430$

变速箱 Transmission

- **型号 Mode:** 9JS150T-B
- **品牌 Brand:** FAST
- **档位排布形式 Gear position:** R 1 3 5 7
L 2 4 6 8
- **各档速比 Transmission ratio:** I 12.65, II 8.38, III 6.22, IV 4.57, V 3.4, VI 2.46, VII 1.83, VIII 1.34, IX 1

前桥 Front axle

- **形式 Modle:** " I "style break face
- **最大承载能力 Maximum capacity (Kg):** 6500

后桥 Rear axle

- **形式 Mode:** 斯太尔 Steyr Technology
- **速比 Ratio:** 4.8
- **最大承载能力 Maximum capacity (Kg):** 13000

转向 Steering

- **形式 Type:** BOSCH

供油 Oil

- **油箱材质 Fuel tank material:** 铝合金 Aluminum alloy
- **油箱容量 Fuel tank capacity (L):** 400

制动 Brake

- 形式 Type: 双回路气制动Dual-circuit air brake

轮胎 Tire

- 型号 Model: 12R22.5 18PR

悬架（前/后） Suspension

- 形式 Type: parabolic leaf spring 10/12
- 后桥稳定杆 Rear axle stabilizer bar: 带 with

电气 Electrical System

- 蓄电池 Batteries: 12 volt-140Ah×2
- 发电机 Alternator: 28 volt / 70 amp
- 起动机 Starter: 24 volt / 5.4 KW

水罐参数 Tanker specification

- Tank volume: 20m³
- Tank material: stainless steel (food grade) ,5 mm
- With pump and flow meter, as well as stainless steel pipe for water supply.
- Pump capacity: 60m³/ hour (mechanical pump)