

CRANE TRUCK 5 TON - USD\$79,792

N.B Prices are subject to change without prior notice.



Specification for 5T Crane Truck

Chassis

- 品号 : LE700
- 室型式 Cab: king
- 型 : HFC5120KN
- 左右舵 (L/R): R

主要技术参数Main technical parameters

整尺寸参数size Parametes

- 外型尺寸 (L×W×H) Overall Dimensions (mm): 8415×2442×2570
- 外型尺寸 (高) Chassis Dimensions (mm) : 8230×2345×2555
- 距Wheelbase (mm) : 4700
- 距 (前/后) Tread (front / rear)FT/RT (mm) : 1700/1800
- (前/后) FF/RF (mm) : 1180/2535
- Chassis FF/RF (mm) : 1180/2350
- 最小离地隙Min Ground Clearance (mm) : 235
- 架上平面离地高度Frame ground clearance H1 (mm) : 908
- 室外cab wide W1 (mm) : 1995

量参数Quality Parameters

- 厂定最大量GVW (Kg) : 12000
- 整整量 Curb Weight (Kg) : 5135

性能参数Performance Parameters

- 最高速 Max speed (Km/h) : 100
- 最大爬坡度 Maximum Gradeability (%) : 30
- 最小半径 Min Turning Radius (m) : 10.5

主配置Main Configuration

机Engine

- 型号Model: B170 33
- 排放准 Emission: III
- 型式 Type: in line-6,ind-cooler turbocharged, diesel
- 定功率/速Max power (Kw/rpm): 125/2500
- 最大扭矩/速 Max torque (N·m/rpm) : 560/1300
- 排量 Displacement (cc) : 5900

离合器 Clutch

- 型式Type: Dry single plate with diaphragm spring
- 直径 Diameter: Φ 380
- 离合助力形式clutch assistance type: clutch assistance

速箱Transmission

- 型号Model: 6DS60T-D
- 档位排布形式Gear Position: 1 3 5 R 2 4 6

- 速比 Ratio: I: 6.64
II: 4.01
III: 2.42
IV: 1.520
V: 1.000
VI: 0.78
R: 6.11

前Front Axle

- 型号Model: 3000LE352
- 定承能力axle capacity (Kg): 3500

KEY : √:Standard Equipment ○:Optional ×:Not Available

后Rear axle

- 速比 Rear axle ratio: 5.125
- 定承能力axle capacity (Kg): 9000

向steering

- 向器形式steering: recirculating ball-type
- 力向 power steering: √

架Suspension

- 型式 Type: front/rear leaf spring
- 板簧片数 (前/后) Leaf spring number(front/rear): 7/10+10

- 后定杆Rear axle stabilizer bar: ×

架Frame

- 架外Wf(前/后) (mm) : 230×75×6
- 架断面尺寸Frame Section Size (Hf*Wf*Hf) (mm) : 877/865

油箱Oil tank

- 油箱材 Fuel tank material: iron
- 油箱容Fuel tank capacity (L) : 200

制Brake

- 形式 Type: air brake
- 干燥器 Dryer: √
- 制器尺寸 (前/后) Drum diameter(front/rear): Φ400/Φ400
- 排Exhaust Braking : √
- 感比例SABS; ×
- 制防抱死系ABS: ×

胎Tire

- 胎型号Model: 255/70R22.5

箱cargo

- 箱 Iron cargo: √
- 竹胶板箱Bamboo cargo: ×

KEY : √:Standard Equipment ○:Optional ×:Not Available

器Electrical

- 蓄池Batteries: 2x80A·h
- 机 Alternator: 28V 70A
- 起机 Starter: 24V 6KW

品配置Product Configuration

安全配置safety configuration

- 倒警器Reverse alarm: √
- 安全警示 Seat Belt warning: √
- 巡航系 Cruise control system: ×
- 行Car driving recorder: ×
- 中控Central locking: ×
- 普通安全 common seat belts: √
- 高度可式安全Height adjustable seat belts: ×
- 安全气囊 Air Bags: ×

音响Acoustical equipment

- 收放机 Radio+MP3: √
- CD: ×

空 Air Condition

- 空Air Condition: ○

- 暖 warm air: ○

内Interior

- 手窗 manual window: √
- 窗 power window: ○
- 分体棚 Fission ceiling: √
- 整体式棚 Overall ceiling: ×
- 通 roof ventilator: ○
- 布座椅 Fabric seat: √
- 短座椅 Linter seat: ×

Body

- 箱尺寸 5300*2240*550mm: Box inner size: 5300*2240*550mm
- 吊机型号 : 徐工SQ5SK3Q : Crane Machine: SQ5SK3Q, XCGM brand
- 最大起重 : 5吨: Max. Lifting Weight: 5T
- 腔后支腿: With supporting rear leg (single cavity)