

REFRIGERATOR TRUCK- 9T 35m³ - USD\$88,210

**N.B. PRICES ARE SUBJECT TO CHANGE BASED ON
THE EXCHANGE RATE.**



SPECIFICATION FOR HFC5121KN

Chassis

- 产品设计号: LG01F
- 驾驶室型式: King
- 车型: HFC5121KN
- 左右舵 (L/R) : L

主要技术参数Main technical parameters

整车尺寸参数size Parameters

- 外型尺寸 (L×W×H) Overall Dimensions (mm) : 9000*2500*2725
- 二类车外型尺寸 (长×宽×高) Chassis Dimensions (mm) : 8795*2235*2585
- 货箱尺寸Box size(inner) (长×宽×高) (mm) : 6750×2300×600
- 轴距Wheelbase (mm) : 5300
- 轮距 (前/后) Tread (front / rear) FT/RT (mm): 1855/1800
- 悬长 (前/后) FF/RF (mm) : 1290/1800
- 二类车悬长Chassis FF/RF (mm) : 1290/2410
- 最小离地间隙Min Ground Clearance (mm): 245
- 车架上平面离地高度Frame ground clearance H1 (mm) : 925

质量参数Quality Parameters

- 厂定最大总质量GVW (Kg) : 15000
- 整车整备质量 Curb Weight (Kg) : 5535

性能参数Performance Parameters

- 最高车速 Max speed (Km/h) : 110
- 最大爬坡度 Maximum Gradeability (%) : 30
- 最小转弯半径 Min Turning Radius (m) : 11

主配置Main Configuration

发动机Engine

- 型号Model: ISDe180 30
- 排放标准 Emission: III
- 型式 Type: Common Rail
- 额定功率/转速Max power (Kw/rpm): 132/2500
- 最大扭矩/转速 Max torque (N·m/rpm) : 650 /1200 -1700
- 排量 Displacement (cc) : 4500

离合器 Clutch

- 型式Type: Dry single plate with diaphragm spring
- 直径 Diameter: $\Phi 395$
- 离合助力形式clutch assistance type: hydraulic assistance

变速箱Transmission

- 型号Model: 6DS70T
- 档位排布形式Gear Position: R 1 3 5
2 4 6
- 速比 Ratio: I : 5.94
II: 3.58
III: 2.15
IV: 1.36
V: 1
VI: 0.77
R: 5.47

前桥 Front Axle

- 型号Model: 3000LG010
- 额定承载能力axle capacity (Kg): 3500

后桥Rear axle

- 速比 Rear axle ratio: 4.875
- 额定承载能力axle capacity (Kg): 9000

转向steering

- 转向器形式steering: recirculating ball-type
- 动力转向 power steering: \checkmark

悬架Suspension

- 型式 Type: front/rear leaf spring
- 板簧片数 (前/后) Leaf spring number(front/rear): 10/9+7
- 后桥稳定杆Rear axle stabilizer bar: √

车架Frame

- 车架外宽Wf(前/后) (mm) : 877/865
- 车架断面尺寸Frame Section Size (Hf*Wf*Hf) (mm) : 230*75*6

油箱Oil tank

- 油箱材质 Fuel tank material: iron
- 油箱容积Fuel tank capacity (L) : 210

制动 Brake

- 形式 Type: air brake
- 干燥器 Dryer: √
- 制动器尺寸 (前/后) Drum diameter(front/rear): $\Phi 400/\Phi 400$
- 排辅Exhaust Braking: √
- 感载比例阀SABS: ×
- 制动防抱死系统 ABS: ×

轮胎Tire

- 轮胎型号Model: 9.00R20

货箱cargo

- 铁货箱 Iron cargo: √
- 竹胶板货箱Bamboo cargo: ×

电器Electrical

- 蓄电池Batteries: 2×12V 100AH
- 发电机Alternator: 28V 70A
- 起动机 Starter: 24V 6KW

KEY: √: Standard Equipment ○:Optional ×:Not Available

产品配置product configuration

安全配置safety configuration

- 倒车报警器Reverse alarm: √
- 安全带警示 Seat Belt warning: √
- 巡航系统 Cruise control system: √
- 行车记录仪Car driving recorder: ×
- 中控门锁 Central locking: √
- 普通安全带 common seat belts: ×
- 高度可调式安全带Height adjustable seat belts: √
- 安全气囊 Air Bags: ×

音响Acoustical equipment

- 收放机 Radio+MP3: √
- CD: ×

空调 Air Condition

- 空调 Air Condition: √
- 暖风 warm air: ○

内饰Interior

- 手动门窗mannal window: ○
- 电动门窗 power window: √
- 分体顶棚Fission ceiling: ×
- 整体式顶棚Overall ceiling: √
- 顶通风 roof ventilator: ×

- 织布座椅Fabric seat: √
- 短绒座椅 Linter seat: ×

Body

- 箱体内尺寸6600*2300*2300: **Box inner size:6600*2300*2300**
- 内外2.0mm玻璃钢+保温材料: **Box material: 2.0mm GRP(glass fiber reinforced plastics) and thermal insulation material**
- 壁厚80mm: **Thickness: 80mm**
- 箱体内配扣板和紧绳器（镀锌）: **With buckle and twine tensioner (galvanized)**
- 制冷温度-15度: **Lowest cooling temperature:-15°C**