

JAC TRACTOR WITH 40m³ TANKER

- ✓ TRACTOR ONLY USD\$83,798
- ✓ TANKER TRAILER USD\$55,906

- Tank volume: 40m³
- Tank material: Q235 **carbon steel**, 4mm
- 3 axes of 13 tons
- Tire: 12.00 tubeless tire
- A food-grade anti-corrosion coating on the inner wall of the tank for transporting potable water

**N.B. PRICES ARE SUBJECT TO CHANGE BASED ON
THE EXCHANGE RATE.**





SPECIFICATION FOR HFC4250K3R1

- 车型 Model: HFC4250K3R1
- 驱动形式 Drive mode: 6×4

尺寸参数Size Parameter

- 轴距 Wheelbase (mm) : 3300+1350
- 轮距 (前/后) Front Tread/Rear Tread (mm) : 2040/1860
- 悬长 (前/后) FF/AF (mm) : 1495/770

上装Refitted

- 牵引器厂家和牵引销直径Retractor Brand and Tractor pin diameter (mm): JOST 50/90

质量参数Quality Parameters

- 额定总质量GCW (Kg) : 48780
- 二类底盘质量 Chassis weight (Kg) : 8650
- 准拖挂车总质量 (Kg) : 40000

性能参数 Performance Parameters

- 最高车速 Max speed (Km/h) : 110
- 最大爬坡度 Maximum Gradeability (%) : 27
- 最小转弯半径 Radius of turning (m) : ≤9

主配置 Main configuration

驾驶室 Cab

- 型式 Type: N944 Half height Roof N944 High Roof
- 座椅 Seat: Air seat
- 发动机防护罩 Engine guard: 标配 standard
- 导流罩 Shroud: 高顶标配、半高顶无standard with Height Roof Cab
- 空调 AC: 标配 standard
- 暖风 Heater: 标配 standard
- 电动玻璃 Electric glass: 标配 standard
- MP3: 标配 standard
- 驾驶室支撑形式 Cabin suspension: 2 springs in front and 2 air bags in rear
- 副驾驶遮阳板 Copilot visor: 标配 standard

车身附件 Body accessories

- 工具箱 Tool box: 标配 standard
- 扶梯 Escalator: 标配 standard
- 中桥上挡泥板 Front fender of middle axle: 标配 standard

发动机 Engine

- 品牌 Brand: WEICHAI
- 型号 Model: WP10.340E32
- 排放水平 Emission levels: E-III
- 额定功率/转速 Max output power (hp/rpm) : 340/2200
- 最大扭矩/转速 Max torque (N·m/rpm) : 1350/1200-1600

- 排量 Displacement (cc) : 9726
- 油泵 Oil pump: Domestic

离合器 Clutch

- 形式 Mode: 单片, 干式, 膜片弹簧式 Single, dry plate diaphragm spring
- 规格 Specification: $\Phi 430$

变速箱 Transmission

- 品牌 Brand: FAST
- 型号 Mode: 12JSD160TA
- 档位排布形式 Gear position: R2/R1 7/1 9/3 11/5
8/2 10/4 12/6
- 速比 Gear ratio: 12.1/0.78
- 取力器 PTO: QH50

前桥 Front axle

- 形式 Modle: " I "style break face
- 最大承载能力 Maximum capacity (Kg): 2*13000

后桥 Rear axle

- 形式 Mode: Steyr Technology
- 速比 Ratio: 4.8
- 最大承载能力 Maximum capacity (Kg): 13000

传动轴 driveshaft

- 规格 Specification: $\Phi 110 \times 6$

转向 Steering

- **形式** Type: 动力转向配BOSCH转向器 Power steering with BOSCH Steering gear

供油 Oil

- **油箱材质** Fuel tank material: 铝合金 Aluminium alloy
- **油箱容量** Fuel tank capacity (L): 400

制动 Brake

- **形式** Type: 双回路气制动Dual-circuit air brake
- **ABS**: 标配 standard

轮胎 Tire

- **型号** Model: 12R22.5 18PR

悬架（前/后） Suspension

- **形式** Type: parabolic leaf spring $\frac{3}{4}$
- **前桥稳定杆** Front axle stabilizer bar: 标配 standard
- **后桥稳定杆** Rear axle stabilizer bar: 标配 standard

Tachograph

- 标配Standard

水罐半挂参数 Tanker trailer specification

- Tank volume: 40m³
- Tank material: Q235 carbon steel, 4mm
- 3 axes of 13 tons
- Tire: 12.00 tubeless tire
- A food-grade anti-corrosion coating on the inner wall of the tank for transporting potable water