

JAC 15m³ TANKER USD\$75,270

N.B. PRICES ARE SUBJECT TO CHANGE BASED ON THE EXCHANGE RATE.





JAC 15m³ TANKER SPECIFICATION

车型 Model: HFC1160KR1T

驱动形式 Drive mode: 4×2

主要技术参数Main technical parameters

尺寸参数Size Parameter

- 外型尺寸 Overall dimension (L×W×H) (mm) :
9000×2450×2993
- 轴距 Wheelbase (mm) : 5300
- 轮距 (前/后) Front Tread/Rear Tread (mm) : 1920/1845
- 悬长 (前/后) FF/AF (mm) : 1530/1950

质量参数Quality Parameters

- 厂定最大总质量 GVW (Kg) : 18000
- 整车整备质量 Curb Weight (Kg) (chassis only): 5800
- 额定载质量 Rated load (kg) : 12200

性能参数 Performance Parameters

- 最高车速 Max speed (Km/h) : 120
- 最大爬坡度 Maximum Gradeability (%) : 40
- 最小转弯半径 Radius of turning (m) : ≤10

主配置 Main configuration

驾驶室 Cab

- 型式 Type: half high roof
- 气垫座椅 Air seat: 标配 standard
- 发动机防护罩 Engine guard: 标配 standard
- 导流罩 Shroud: 标配 standard
- 空调 AC: 标配 standard
- 暖风 Heater: 标配 standard
- 电动玻璃 Electric glass: 标配 standard
- MP3: 标配 standard
- 驾驶室支撑形式 Cabin suspension: 2 springs in front and 2 rubber pad in rear
- 副驾驶遮阳板 Copilot visor: 标配 standard

发动机 Engine

- 品牌 Brand: CUMMINS
- 型号 Model: ISDe 285 30
- 排放水平 Emission levels: E-III
- 额定功率速 Max output power: 210/2500
- 最大扭矩/转速 Max torque (N·m/rpm) : 970/1200-1700

- 排量 Displacement (cc) : 6700

离合器 Clutch

- 形式 Mode: 单片、干式, 膜片弹簧 Single, dry plate, diaphragm spring
- 规格 Specification: $\Phi 430$

变速箱 Transmission

- 品牌 Brand: FAST
- 型号 Mode: 8JS105TA
- 档位排布形式 Shift type: RH/RL 5/1 7/3
6/2 8/4
- 速比 Gear ratio: I档: 8.08/5.66:
II档: 3.98/2.86
III档: 2.03/1.42
IV档: 1.00/0.72
RL 档: 8.24
RH 档: 2.07
- 取力器 PTO: QCD45A

前桥 Front axle

- 形式 Modle: “工 “style break face
- 最大承载能力 Maximum capacity (Kg): 5000

后桥 Rear axle

- 形式 Mode: 457
- 速比 Ratio: 5.286
- 最大承载能力 Maximum capacity (Kg): 13000

传动轴 driveshaft

- 规格 Specification: $\Phi 110 \times 6$

转向 Steering

- **形式** Type: 动力转向配国产转向器 Power steering with domestic Steering gear

供油 Oil

- **油箱材质** Fuel tank material: 铝合金 Aluminum alloy
- **油箱容量** Fuel tank capacity (L): 200L

制动 Brake

- **形式** Type: 双回路气制动 Dual-circuit air brake
- **制动器直径 (mm)** Drum diameter: $\Phi 400$
- **ABS**: 标配 standard
- **轮间差速锁** Inter-wheel differential lock: 标配 standard

轮胎 Tire

- **型号** Model: 11R22.5 16PR

悬架 (前/后) Suspension

- **形式** Type: parabolic leaf spring 9/9+7
- **前桥稳定杆** Front axle stabilizer bar: 标配 standard
- **后桥稳定杆** Rear axle stabilizer bar: 标配 standard

电气 Electrical System

- **蓄电池** Batteries: 12 volt-120Ah×2
- **发电机** Alternator: 28 volt / 70 amp
- **起动机** Starter: 24 volt /6.0kW

行车记录仪 Tachograph

- 标配 standard

水罐参数 Tanker specification

- Tank volume: 15m³
- Tank material: Q235 carbon steel, 4mm
- A food-grade anti-corrosion coating on the inner wall of the tank for transporting potable water
- With pump and flow meter, as well as stainless