

JAC 20m³ (Weichai) Carbon steel TANKER
USD\$93,390

- Tank volume: 20m³
- Tank material: Q235 carbon steel, 5mm
- A food-grade anti-corrosion coating on the inner wall of the tank for transporting potable water
- With pump and flow meter, as well as stainless steel pipe for water supply
- Pump capacity: 60m³/ hour (mechanical pump)

N.B. PRICES ARE SUBJECT TO CHANGE BASED
ON THE EXCHANGE RATE.





Specification for HFC1254KR1T

- 车型 Model: HFC1254KR1T
- 驱动形式 Drive mode: 6×4

主要技术参数Main technical parameters

尺寸参数Size Parameter

- 外型尺寸 Overall dimension (L×W×H) (mm) :
11200×2500×3430
- 轴距 Wheelbase (mm) : 6000+1350

性能参数Performance Parameters

- 最高车速 Max speed (Km/h) : 90
- 最大爬坡度 Maximum Gradeability (%) : 40

主配置 Main configuration

驾驶室 Cab

- 型式 Type: Half height roof
- 座椅 Seat: air seat
- 空调 AC: 标配Standard
- 暖风 Heater: 标配Standard
- 电动玻璃 Electric glass: 标配Standard
- MP3: 标配Standard
- 驾驶室支撑形式 Cabin suspension: 2 springs in front and 2 air bags in rear
- 副驾驶遮阳板 Copilot visor: 标配Standard
- 散热器保护架 Radiator protection frame: 带 with

发动机 Engine

- 型号 Model: WP10.340E32
- 品牌 Brand: WEICHAI
- 排放水平 Emission levels: E-III
- 额定功率/转速 Max output power (hp/rpm) : 340/2200
- 最大扭矩/转速 Max torque (N·m/rpm) : 1350/1200-1600
- 排量 Displacement (cc) : 9726

离合器 Clutch

- 形式 Mode: 单片，干式，膜片弹簧式，法雷奥
Single, dry plate, diaphragm spring, VALEO
- 规格 Specification: $\Phi 430$

变速箱 Transmission

- 型号 Mode: 9JS150T-B
- 品牌 Brand: FAST
- 档位排布形式 Gear position: R 1 3 5 7
L 2 4 6 8
- 各档速比 Transmission ratio: I 12.65, II 8.38, III 6.22, IV 4.57, V 3.4, VI 2.46, VII 1.83, VIII 1.34, IX 1

前桥 Front axle

- 形式 Modle: " I "style break face
- 最大承载能力 Maximum capacity (Kg): 6500

后桥 Rear axle

- 形式 Mode: 斯太尔 Steyr Technology
- 速比 Ratio: 4.8
- 最大承载能力 Maximum capacity (Kg): 13000

转向 Steering

- 形式 Type: BOSCH

供油 Oil

- 油箱材质 Fuel tank material: 铝合金 Aluminum alloy
- 油箱容量 Fuel tank capacity (L): 400

制动 Brake

- 形式 Type: 双回路气制动Dual-circuit air brake

轮胎 Tire

- 型号 Model: 12R22.5 18PR

悬架 (前/后) Suspension

- 形式 Type: parabolic leaf spring 10/12
- 后桥稳定杆 Rear axle stabilizer bar: 带 with

电气 Electrical System

- 蓄电池 Batteries: 12 volt-140Ah×2
- 发电机 Alternator: 28 volt / 70 amp
- 起动机 Starter: 24 volt / 5.4 KW

水罐参数 Tanker specification

- Tank volume: 20m³
- Tank material: Q235 carbon steel, 5mm
- A food-grade anti-corrosion coating on the inner wall of the tank for transporting potable water
- With pump and flow meter, as well as stainless steel pipe for water supply
- Pump capacity: 60m³/ hour (mechanical pump)