

**REFUELING TRUCK- 4 m<sup>3</sup>- 4000L**  
**CAPACITY**

**(to transport fuel without refueling machine)**

**USD\$46,956**

**N.B. PRICES ARE SUBJECT TO CHANGE BASED  
ON THE EXCHANGE RATE.**



## **SPECIFICATION FOR HFC5042KN**

### **Chassis**

- 产品设计号 : LD062
- 驾驶室型式: Single
- 车型:HFC5042KN
- 左右舵 (L/R) : R

## **主要技术参数 Main technical parameters**

### **整车尺寸参数size Parameters**

- 外型尺寸 (L×W×H) Overall Dimensions (mm) : 5995\*1900\*2330
- 二类车外型尺寸 (长×宽×高) Chassis Dimensions (mm) :  
5958\*1725\*2215
- 货箱尺寸Box size(inner) (长×宽×高) (mm) : 4230x1790x400
- 轴距Wheelbase (mm) : 3360
- 轮距 (前/后) Tread (front / rear )FT/RT (mm) : 1440/1425
- 悬长 (前/后) FF/RF (mm) : 1110/1525
- 二类车悬长Chassis FF/RF (mm) : 1110/1488
- 最小离地间隙 Min Ground Clearance (mm) : 190
- 车架上平面离地高度Frame ground clearance H1 (mm) : 691
- 驾驶室外宽cab wide W1 (mm) : 1725

### **质量参数Quality Parameters**

- 厂定最大总质量GVW (Kg) : 4490
- 整车整备质量 Curb Weight (Kg) : 2560

## 性能参数Performance Parameters

- 最高车速 Max speed (Km/h) : 100
- 最大爬坡度 Maximum Gradeability (%) : 30
- 最小转弯半径 Min Turning Radius (m) : 7

## 主配置Main Configuration

### 发动机Engine

- 型号Model: HFC4DA1-1
- 排放标准 Emission: II
- 型式 Type: turbocharged
- 额定功率/转速Max power (Kw/rpm): 68/3600
- 最大扭矩/转速 Max torque (N·m/rpm) : 216/1800-2200
- 排量 Displacement (cc) : 2771

### 离合器 Clutch

- 型式Type: Dry single plate with diaphragm spring
- 直径 Diameter:  $\Phi 250$
- 离合助力形式clutch assistance type: vacuum assistance

### 变速箱Transmission

- 型号Model: LC5T255M3
- 档位排布形式Gear Position: 1 3 5  
2 4 R
- 速比 Ratio: I: 5.529  
II: 2.782  
III: 1.641

IV: 1

V: 0.785

VI: -

R: 5.271

### 前桥 Front Axle

- 型号Model: 3000LD060/LD060XZ
- 额定承载能力axle capacity (Kg): 2000

### 后桥 Rear axle

- 速比 Rear axle ratio: 5.375(6.142)
- 额定承载能力axle capacity (Kg): 4000

### 转向steering

- 转向器形式steering: recirculating ball-type
- 动力转向 power steering: √

### 悬架Suspension

- 型式 Type: front/rear leaf spring
- 板簧片数 (前/后) Leaf spring number(front/rear): 7/4+6
- 后桥稳定杆Rear axle stabilizer bar: ×

### 车架Frame

- 车架外宽Wf(前/后) (mm) : 671/700
- 车架断面尺寸Frame Section Size (Hf\*Wf\*Hf) (mm) : 170\*65\*5

### 油箱Oil tank

- 油箱材质 Fuel tank material: plastic
- 油箱容积Fuel tank capacity (L) : 100

## 制动 Brake

- 形式 Type: hydraulic brake
- 干燥器 Dryer: ×
- 制动器尺寸（前/后） Drum diameter(front/rear):  $\Phi 320/\Phi 320$
- 排辅 Exhaust Braking:  $\checkmark$
- 感载比例阀 SABS: ×
- 制动防抱死系统 ABS: ×

## 轮胎 Tire

- 轮胎型号 Model: 6.50R16 10PR  
7.00R16 12 PR  
205/75R17.5 12PR

## 货箱 cargo

- 铁货箱 Iron cargo: ○
- 竹胶板货箱 Bamboo cargo:  $\checkmark$

## 电器 Electrical

- 蓄电池 Batteries: 100A·h
- 发电机 Alternator: 14V 60A
- 起动机 Starter: 12V 2.8kw

**KEY:  $\checkmark$ : Standard Equipment ○: Optional ×: Not Available**

## 产品配置product configuration

### 安全配置safty configuration

- 倒车报警器Reverse alarm: √
- 安全带警示 Seat Belt warning: √
- 巡航系统 Cruise control system: ×
- 行车记录仪Car driving recorder: ×
- 中控门锁 Central locking: ○
- 普通安全带 common seat belts: ×
- 高度可调式安全带Height adjustable seat belts: √
- 安全气囊 Air Bags: ×

### 音响Acoustical equipment

- 收放机 Radio+MP3: √
- CD: ×

### 空调 Air Condition

- 空调 Air Condition: √
- 暖风 warm air: √

**KEY:√:StandardEquipment○:Optional×:NotAvailable**

### 内饰Interior

- 手动门窗 manual window: √
- 电动门窗 power window: ○
- 分体顶棚 Fission ceiling: √
- 整体式顶棚 Overall ceiling: ×
- 顶通风 roof ventilator: ×
- 织布座椅 Fabric seat: √
- 短绒座椅 Linter seat: ×

### Body

- 罐体容积4m<sup>3</sup>: Tank volume: 4 m<sup>3</sup>
- 罐体材质Q235: Tank material:Q235
- 壁厚4mm: Tank thickness: 4 mm
- 泵进泵出: With pump in and out function
- 配一个海底阀: With one sea inlet valve
- 配一个欧标罐盖: With one manhole cover