

**REFRIGERATOR TRUCK- 5T 20m<sup>3</sup> - USD\$67,150**

**N.B. PRICES ARE SUBJECT TO CHANGE BASED ON  
THE EXCHANGE RATE.**



# **SPECIFICATION FOR HFC5081KN**

## **Chassis**

- 产品设计号: LE761
- 驾驶室型式: single
- 车型: HFC5081KN
- 左右舵 (L/R) : R

## **主要技术参数Main technical parameters**

### **整车尺寸参数size Parameters**

- 外型尺寸 (L×W×H) Overall Dimensions (mm) : 7098×2200×2326
- 二类车外型尺寸 (长×宽×高) Chassis Dimensions (mm) : 6835×1995×2324
- 货箱尺寸Box size(inner) (长×宽×高) (mm) : 5175×2006×550
- 轴距Wheelbase (mm) : 3815
- 轮距 (前/后) Tread (front / rear) FT/RT (mm) : 1671/1600
- 悬长 (前/后) FF/RF (mm) : 1110/2173
- 二类车悬长Chassis FF/RF (mm) : 1110/1910
- 最小离地间隙Min Ground Clearance (mm) : 195
- 车架上平面离地高度Frame ground clearance H1 (mm) : 731
- 驾驶室外宽cab wide W1 (mm) : 1995

### **质量参数Quality Parameters**

- 厂定最大总质量GVW (Kg) : 7500
- 整车整备质量 Curb Weight (Kg) : 3350

### **性能参数Performance Parameters**

- 最高车速 Max speed (Km/h) : 95
- 最大爬坡度 Maximum Gradeability (%) : 30
- 最小转弯半径 Min Turning Radius (m) : 7.5

## 主配置Main Configuration

### 发动机Engine

- 型号Model: B125 33
- 排放标准 Emission: II
- 型式 Type: in line-4,int-cooler turbocharged,diesel
- 额定功率/转速Max power (Kw/rpm): 92 (125hp) /2800
- 最大扭矩/转速 Max torque (N·m/rpm) :410/1500
- 排量 Displacement (cc) : 3920

### 离合器 Clutch

- 型式Type: Dry single plate with diaphragm spring
- 直径 Diameter:  $\Phi$ 350
- 离合助力形式clutch assistance type: clutch assistance

### 变速箱Transmission

- 型号Model: LC6T450M1
- 档位排布形式Gear Position: R 1 3 5  
2 4 6
- 速比 Ratio: I: 6.314  
II: 3.913  
III: 2.262  
IV: 1.393  
V: 1  
VI: 0.788  
R: 5.874

## 前桥Front Axle

- 型号Model: 3000LE761
- 额定承载能力axle capacity (Kg): 2500

## 后桥 Rear axle

- 速比 Rear axle ratio: 4.778
- 额定承载能力axle capacity (Kg): 6000

## 转向steering

- 转向器形式steering: recirculating ball-type
- 动力转向 power steering: √

## 悬架Suspension

- 型式 Type: front/rear leaf spring
- 板簧片数（前/后） Leaf spring number(front/rear): 8/6+6
- 后桥稳定杆Rear axle stabilizer bar: ×

## 车架Frame

- 车架外宽Wf(前/后) (mm) : 935/750
- 车架断面尺寸Frame Section Size (Hf\*Wf\*Hf) (mm) : 190\*65\*6

## 油箱Oil tank

- 油箱材质 Fuel tank material: 铝合金
- 油箱容积Fuel tank capacity (L) : 130

## 制动 Brake

- 形式 Type: air brake
- 干燥器 Dryer: √
- 制动器尺寸（前/后） Drum diameter(front/rear): Φ320/Φ320
- 排辅 Exhaust Braking: √
- 感载比例阀SABS: ×
- 制动防抱死系统 ABS: ×

## 轮胎Tire

- 轮胎型号 Model: 8.25R16  
215/75R17.5

## 货箱cargo

- 铁货箱 Iron cargo: √
- 竹胶板货箱 Bamboo cargo: ×

## 电器Electrical

- 蓄电池 Batteries: (12V 80Ah)\*2
- 发电机 Alternator: 28V 70A
- 起动机 Starter: 24V 5KW

**KEY: √: Standard Equipment ○:Optional ×:Not Available**

## 产品配置product configuration

### 安全配置safety configuration

- 倒车报警器Reverse alarm: √
- 安全带警示 Seat Belt warning: ×
- 巡航系统 Cruise control system: ×
- 行车记录仪Car driving recorder: ×
- 中控门锁 Central locking: ×
- 普通安全带 common seat belts: √
- 高度可调式安全带Height adjustable seat belts: ○
- 安全气囊 Air Bags: ×

### 音响Acoustical equipment

- 收音机 Radio+MP3: √
- CD: ×

**KEY: √:Standard Equipment ○:Optional ×:Not Available**

### 内饰Interior

- 手动门窗mannal window: √
- 电动门窗 power window: ○
- 分体顶棚Fission ceiling: √
- 整体式顶棚Overall ceiling: ×
- 顶通风 roof ventilator: √
- 织布座椅Fabric seat: √
- 短绒座椅 Linter seat: ×

## **Body**

- 箱体内尺寸5100\*2000\*2000: **Box inner size:5100\*2000\*2000mm**
- 内外2.0mm玻璃钢+保温材料: **Box material: 2.0mm GRP(glass fiber reinforced plastics) and thermal insulation material**
- 壁厚80mm: **Thickness: 80mm**
- 箱体内配扣板和紧绳器（镀锌）: **With buckle and twine tensioner(galvanized)**
- 制冷温度-18度: **Lowest cooling temperature:-18°C**