

SPRINKLING TRUCK 6m³- USD\$49,986

**N.B. PRICES ARE SUBJECT TO CHANGE BASED
ON THE EXCHANGE RATE.**



Specification for HFC5081KN

Chassis

- 产品设计号: LE761
- 驾驶室型式: single
- 车型: HFC5081KN
- 左右舵 (L/R) : R

主要技术参数Main technical parameters

整车尺寸参数size Parameters

- 外型尺寸 (L×W×H) Overall Dimensions (mm) : 7098×2200×2326
- 二类车外型尺寸 (长×宽×高) Chassis Dimensions (mm) : 6835×1995×2324
- 货箱尺寸Box size(inner) (长×宽×高) (mm) : 5175×2006×550
- 轴距Wheelbase (mm) : 3815
- 轮距 (前/后) Tread (front / rear) FT/RT (mm) : 1671/1600
- 悬长 (前/后) FF/RF (mm) : 1110/2173
- 二类车悬长Chassis FF/RF (mm) : 1110/1910
- 最小离地间隙Min Ground Clearance (mm) : 195
- 车架上平面离地高度Frame ground clearance H1 (mm) : 731
- 驾驶室外宽cab wide W1 (mm) : 1995

质量参数Quality Parameters

- 厂定最大总质量GVW (Kg) : 7500
- 整车整备质量 Curb Weight (Kg) : 3350

性能参数Performance Parameters

- 最高车速 Max speed (Km/h) : 95
- 最大爬坡度 Maximum Gradeability (%) : 30
- 最小转弯半径 Min Turning Radius (m) : 7.5

主配置Main Configuration

发动机Engine

- 型号Model: B125 33
- 排放标准 Emission: II
- 型式 Type: in line-4,int-cooler turbocharged,diesel
- 额定功率/转速Max power (Kw/rpm): 92 (125hp) /2800
- 最大扭矩/转速 Max torque (N·m/rpm) : 410/1500
- 排量 Displacement (cc) : 3920

离合器 Clutch

- 型式Type: Dry single plate with diaphragm spring
- 直径 Diameter: Φ 350
- 离合助力形式clutch assistance type: clutch assistance

变速箱Transmission

- 型号Model: LC6T450M1
- 档位排布形式Gear Position: R 1 3 5
2 4 6
- 速比 Ratio: I: 6.314
II: 3.913
III: 2.262
IV: 1.393
V: 1
VI: 0.788
R: 5.874

前桥 Front Axle

- 型号Model: 3000LE761
- 额定承载能力axle capacity (Kg): 2500

后桥Rear axle

- 速比 Rear axle ratio: 4.778
- 额定承载能力axle capacity (Kg): 6000

转向steering

- 转向器形式steering: recirculating ball-type
- 动力转向 power steering: √

悬架Suspension

- 型式 Type: front/rear leaf spring
- 板簧片数（前/后） Leaf spring number(front/rear): 8/6+6
- 后桥稳定杆Rear axle stabilizer bar: ×

车架Frame

- 车架外宽Wf(前/后) (mm) : 935/750
- 车架断面尺寸Frame Section Size (Hf*Wf*Hf) (mm) : 190*65*6

油箱Oil tank

- 油箱材质 Fuel tank material: 铝合金
- 油箱容积Fuel tank capacity (L) : 130

制动 Brake

- 形式 Type: air brake
- 干燥器 Dryer: √
- 制动器尺寸（前/后） Drum diameter(front/rear): $\Phi 320/\Phi 320$
- 排辅Exhaust Braking: √
- 感载比例阀SABS: ×
- 制动防抱死系统 ABS: ×

轮胎Tire

- 轮胎型号Model: 8.25R16
215/75R17.5

货箱cargo

- 铁货箱 Iron cargo: √
- 竹胶板货箱Bamboo cargo: ×

电器Electrical

- 蓄电池Batteries: (12V 80Ah)*2
- 发电机Alternator: 28V 70A
- 起动机 Starter: 24V 5KW

KEY: √: Standard Equipment ○: Optional ×: Not Available

产品配置product configuration

安全配置safety configuration

- 倒车报警器Reverse alarm: √
- 安全带警示 Seat Belt warning: ×
- 巡航系统 Cruise control system: ×
- 行车记录仪Car driving recorder: ×
- 中控门锁 Central locking: ×
- 普通安全带 common seat belts: √
- 高度可调式安全带Height adjustable seat belts: ○
- 安全气囊 Air Bags: ×

音响Acoustical equipment

- 收放机 Radio+MP3: √
- CD: ×

空调 Air Condition

- 空调 Air Condition: ○
- 暖风 warm air: √

内饰Interior

- 手动门窗 manual window: √
- 电动门窗 power window: ○
- 分体顶棚 Fission ceiling: √
- 整体式顶棚 Overall ceiling: ×
- 顶通风 roof ventilator: √
- 织布座椅 Fabric seat: √
- 短绒座椅 Linter seat: ×

Body

- 罐体容积 6m³: Tank volume: 6 m³
- 罐体材质 Q235: Tank material: Q235
- 壁厚 4mm: Tank thickness: 4 mm
- 泵进泵出: With pump in and out function
- 前冲后洒: Flushing in the front and sprinkling in the back type
- 尾部带作业平台和高炮: With working platform and water cannon in the back