

REFUELING TRUCK – 2.5m³- 2500L CAPACITY

(with refuelling gun) USD\$50,145.80

**N.B PRICES ARE SUBJECT TO CHANGE BASED ON THE
EXCHANGE RATE**



Specifications of 2500L (2.5m³) Refueling Truck

产品设计号: LD410

驾驶室型式 Cab : Single

车型Model: HFC5050K

左右舵 (L/R): R

轴距Wheelbase (mm): 2800

轮距 (前/后) Tread (front / rear)FT/RT (mm) :1440/1395

悬长 (前/后) FF/RF (mm): 1110/1498

二类车悬长Chassis FF/RF (mm): 1110/1498

最小离地间隙Min Ground Clearance (mm) :200

车架上平面离地高度Frame ground clearance H1 (mm) : 667

驾驶室外宽cab wide W1 (mm) : 1725

质量参数Quality Parameters

厂定最大总质量GVW (Kg) : 4100

第一轴/第二轴整备质量 Front axle/Rear axle (Kg) :1310/990

性能参数Performance Parameters

最高车速 Max speed (Km/h) :95

最大爬坡度 Maximum Gradeability (%) :30

最小转弯半径 Min Turning Radius (m) :6

主配置Main Configuration

发动机Engine

型号Model: HFC4DA1-1

排放标准 Emission: II

型式 Type "in line-4,int-cooler turbocharged, diesel"

额定功率/转速Max power (Kw/rpm): 68/3600

最大扭矩/转速 Max torque (N·m/rpm) :216/1800-2000

排量 Displacement (cc) : 2771

离合器 Clutch

型式Type: Dry single plate with diaphragm spring

直径 Diameter: Φ 250

离合助力形式clutch assistance type: ×

变速箱Transmission

型号Model: LC5T255M3

档位排布形式Gear Position: 1 3 5

2 4 R

| | |
|-------------|-------|
| 速比 Ratio: I | 5.529 |
| II | 2.782 |
| III | 1.641 |
| IV | 1.000 |
| V | 0.785 |
| VI | |
| R | 5.271 |

前桥 Front Axle

型号Model: 3000D870/LD410

额定承载能力axle capacity (Kg): 2000

后桥 Rear axle

速比 Rear axle ratio: 6.142

额定承载能力axle capacity (Kg): 4000

转向steering

转向器形式steering: recirculating ball-type

动力转向 power steering:

悬架Suspension

型式 Type : front/rear leaf spring

板簧片数 (前/后) Leaf spring number(front/rear):11/9+7

后桥稳定杆Rear axle stabilizer bar: ×

车架Frame

车架外宽Wf (前/后) (mm) : 760/680

车架断面尺寸Frame Section Size (Hf*Wf*Hf) (mm) : 170*65*5

油箱Oil tank

油箱材质 Fuel tank material: iron

油箱容积Fuel tank capacity (L) : 100

制动 Brake

形式 Type: hydraulic brake

干燥器 Dryer: ×

制动器尺寸 (前/后) Drum diameter(front/rear): $\Phi 320/\Phi 320$

排辅Exhaust Braking: \checkmark

感载比例阀SABS : ×

制动防抱死系统 ABS: ×

轮胎Tire

轮胎型号 Model: 7.00R16 12PR 6.50R16 10PR

电器Electrical

蓄电池Batteries: 12V-100Ah

发电机Alternator: 14V 60A

起动机 Starter: 12V 2.8kw

产品配置product configuration

安全配置safety configuration

倒车报警器Reverse alarm :√

安全带警示 Seat Belt warning:√

巡航系统 Cruise control system:×

行车记录仪Car driving recorder:×

中控门锁 Central locking:√

普通安全带 common seat belts: √

高度可调式安全带Height adjustable seat belts:×

安全气囊 Air Bags:×

音响Acoustical equipment

收放机 Radio+MP3:√

CD: ×

空调 Air Condition

空调 Air Condition: √

电动门窗 power window: √

分体式顶棚Fission ceiling: √

整体式顶棚Overall ceiling: ×

顶通风 roof ventilator: √

织布座椅Fabric seat: √

短绒座椅 Linter seat: ×

上装 Refitting

罐体容积2.5m³: Tank volume: 2.5 m³

罐体材质Q235: Tank material:Q235

壁厚4mm: Tank thickness: 4 mm

泵进泵出: With pump in and out function

配一个海底阀: With one sea inlet valve

配一个欧标罐盖: With one manhole cover (European standard)

配正星加油机: With refueling machine

配15米卷盘加油枪: With refueling gun (15 meters)